SUREGRIP® 134 CLAY STRIPPABLE WALLCOVERING ADHESIVE

DESCRIPTION AND USES

SureGrip® 134 Clay Strippable Wallcovering Adhesive is a commercial grade, ready-to-use, clay-based formulated with a high solids/low moisture content for installing medium to heavyweight vinyl or non-vinyl materials (up to 40 oz. commercial grade types I, II and III) and special wallcoverings such as flexible wood, fabric-backed foil and Mylar®.

SureGrip 134 is a non-dilution clay formula designed to flow easily through pasting machines without the need to add water and offers excellent wet tack for easy positioning of heavy materials. It is suitable for use with moisture sensitive wallcoverings to prevent bubbling, seam curling and edge lifting. SureGrip 134 is easy to clean up and will allow fabric-backed and other strippable types of wallcoverings applied over primed or bare drywall to strip easily.

SureGrip 134 is not recommended for hanging lightweight wallpaper or delicate wallcoverings such as silk, burlap, grass cloth, strings, or fabric that may stain easily. It is not intended for use to hang borders or wallcoverings over existing vinyl wallcovering without the use of a primer. See "Existing Vinyl Wallcovering" under Application in next column for recommendations.

PERFORMANCE CHARACTERISTICS

- For use with all wallcovering types (heavy commercial vinyl to delicate materials)
- Excellent wet tack and slip for easy positioning
- Extended open time for trouble-free booking and double-cutting
- Non-staining, easy clean-up
- Spreads and flows easily – Ideal for pasting machines
- Mold & mildew resistant adhesive

PRODUCTS

SKU	Container Size
02901	1-Gallon
02900	5-Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces must be clean, dry, sound and free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Inspect the surface for paint bonding, loose wallcoverings, damaged wallboard or plaster. Remove old or loose wallcovering and residual wallcovering adhesive with DIF® Wallpaper Stripper. Repair unsound surfaces. Seal loose paint or damaged drywall and cured skim coats with Gardz® High Performance Sealer as needed.

PRODUCT APPLICATION (cont.)

Prime all surfaces (including oil-based paints, oil-based primers for painted surfaces and latex or oil-based stain-kill coatings) with an acrylic primer. Use ShieldZ® Universal, ShieldZ® Universal Plus or ShieldZ Clear Acrylic Wall Size.

Mold & Mildew

Eliminate pre-existing mold and mildew by washing the affected area with a solution of ¾ cup of Clorox® bleach to 1 gallon of water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning agents to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

Drywall

Wipe down with a damp cloth to remove residual joint compound dust prior to priming. No primer is required when hanging strippable fabric backed vinyl wallcovering over bare drywall. However, adhesive must fully cure (approximately 4-6 weeks) prior to stripping. If uncertain, priming is always recommended to ensure proper performance.

Plaster

New plaster must age at least 90 days before hanging wallcovering. Prime prior to installation.

Glossy Surfaces

Glossy paint, paneling, metal, glass, plastic, etc. should be primed with ShieldZ® Universal, ShieldZ® Universal Plus or ShieldZ® Clear Acrylic Wall Size prior to wallcovering installation. Metal surfaces should be primed with rust inhibiting Bulls-Eye® 1-2-3 Primer.

Existing Vinyl Wallcovering

This product is not intended for hanging wallcoverings over existing vinyl wallcoverings without the use of a primer. For hanging directly over vinyl without priming, use SureGrip 127 Vinyl over Vinyl Wallcovering Adhesive according to label directions. For hanging lightweight wallpaper or borders directly over unprimed vinyl, use SureGrip Universal Adhesive or SureGrip Border Adhesive for Wallpapered Surfaces.

Textile and Delicate Wallcoverings

Take special care to keep the adhesive off the face of textile or delicate wallcovering. Some wallcovering can be stained by water alone. Test for stain resistance prior to installation and hang according to manufacturer's instructions.

Form: GDH-154
Rev.: 082713

PRODUCT APPLICATION (cont.)

APPLICATION

Use only when temperature is between 50-100°F (10-38°C) and the relative humidity is less than 85%. Adhesive is ready to use. **Do not dilute.** Mix thoroughly before application. Apply an even coat using a roller, brush or pasting machine to the back of the wallcovering. Make sure sufficient adhesive is on edges. Avoid contact with the surface of embossed or delicate wallcovering. Book and hang wallcovering according to the manufacturer's instructions.

COVERAGE

One gallon of adhesive will hang up 6 double rolls or 310 square feet. Spread rate may differ with various backings.

DRY TIME

Drying time will vary depending on the wallcovering types, temperature, ventilation and humidity of the room.

CLEAN-UP

Remove excess adhesive on or around the wallcovering immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

TOOL CLEAN-UP

Clean tools with warm water.

STORAGE

Protect from freezing. Always keep the container tightly closed and store in a cool dry place at temperatures between 40-100°F (4-38°C).

TECHNICAL DATA

SUREGRIP® 134 CLAY STRIPPABLE WALLCOVERING ADHESIVE

PHYSICAL PROPERTIES

	SureGrip 134 Clay Strippable Wallcovering Adhesive
Resin Type	Clay-based Wallcovering Adhesive
Solvents	Water
Appearance	Light Tan
Odor	Mild
Solids by Weight	44-46%
Volatile Organic Compounds	<10 g/l (0.083 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)	310 sq.ft./gal. Depending on porosity and application method
Dry Times at 70-80°F (21-27ºC) and 50% Relative Humidity	Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.
Shelf Life	1 year
Flammability	Non-flammable
Flash Point	>200ºF (93ºC)
Safety	For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-154
Rev.: 082713